

SBP35WC125P2D2B32E

## SWIVEL CASTOR Ø 125 MM SERIES P2D2 (ESD) BALL BEARING

### WHEEL

|                      |  |
|----------------------|--|
| wheel diameter in mm | 125 mm   |
| wheel width in mm    | 40   |
| hub width in mm      | 50   |
| screw size           | M10  |
| tread                | thermopl. rubber 65 - 75° shore A<br>grey, ESD |
| wheel center         | polypropylene grey, ESD                        |
| bearing              | ball bearing                                   |
| threadguard          | small nylon threadguard                        |
| temperature range    | -20°C to +60°C                                 |



### HOUSING

|                                  |              |
|----------------------------------|--------------|
| material thickness fitting in mm | 2.50         |
| material thickness fork in mm    | 2.50         |
| fitting                          | plate        |
| mounting dimension in mm         | 80 / 77 x 60 |
| offset dimension in mm           | 40           |
| total height in mm               | 155          |
| swivel radius in mm              | 0            |
| dyn. load capacity in kg         | 120          |
| test norm                        | DIN EN 12532 |



### CASCOO Europe GmbH

Lütke Haar 15 • 59602 Rüthen • Germany  
+49 2952 - 970629-0  
info@cascoo.eu • www.cascoo.eu