



TPP21WC100N2U6B32

SWIVEL CASTOR WITH TOTAL BRAKE Ø 100 MM SERIES N2U6 BALL BEARING

WHEEL

wheel diameter in mm	100
wheel width in mm	32
hub width in mm	40
screw size	M8
tread	thermopl. polyurethane 95° shore A red
wheel center	polyamide grey
bearing	ball bearing
threadguard	small nylon threadguard
temperature range	-40°C to +80°C



HOUSING

material thickness fitting in mm	3.00
material thickness fork in mm	2.50
fitting	plate
mounting dimension in mm	80 / 77 x 60
offset dimension in mm	40
total height in mm	128
swivel radius in mm	127
dyn. load capacity in kg	150
test norm	DIN EN 12532




CASCOO Europe GmbH

Lütke Haar 15 • 59602 Rüthen • Germany
+49 2952 - 970629-0
info@cascoo.eu • www.cascoo.eu

TPP21WC100N2U6B32

SWIVEL CASTOR WITH TOTAL BRAKE Ø 100 MM SERIES N2U6 BALL BEARING



CASCOO Europe GmbH

Lütke Haar 15 • 59602 Rüthen • Germany
+49 2952 - 970629-0
info@cascoo.eu • www.cascoo.eu